

ACLOSE HS150 SEALER for Adgreencoat

1 GENERIC TYPE

Acrylic Emulsion Sealer.

2 STANDARD

Company Standard

3 APPLICATIONS

External and Internal new concrete, mortar cement render, brickwork, hard and soft board, plaster, ceiling and slate tile etc.

4 FEATURES

- Quick dry.
- Good adhesion property.
- Low odour.
- Excellent Workability.
- Good alkaline resistance.

5 SPECIFICATION DATA

Item		Specification		
No. of Components		1		
Packing Size		13kg (10ℓ)		
Colour		White		
Gloss		Matt		
Specific Gravity(25°C)		1.3		
Viscosity(25°C)		70~80 Krebs Units		
Solids Content(by weight%)		Approx.55 %		
Volume Solid(by volume%)		Approx.40 %		
Drying Time	Temperature	5°C	20°C	30°C
	Surface Dry	60min	30min	20min
	Hard Dry	4h	2h	1h
Flash Point(°C)		-		
Shelf Life		12 months		

6 APPLICATION INSTRUCTIONS

Item		Specification			
Surface Preparation		Refer to NOTES			
Mixing Ratio		-			
Aging Time		-			
Pot Life		-			
Application Method		Brush, Airless Spray			
Thinner		Drinking Water			
Application Conditions	Application Method	Brush, Roller	Spray		
	Dilution Ratio	0~10%	10~20%		
	Theoretical Coverage (at 30µm)	0.1kg/m ² /coat			
		13m ² /L/coat			
Recommended DFT		30µm/coat			
Coating Interval	Temperature	5°C	20°C	30°C	
	Minimum	4h	2h	1h	
	Maximum	7days	7days	7days	

7 NOTES

- Remove dirt, oil, grease and other contamination from the surface. Ensure substrate pH<10 and moisture content<10%
- Stir the material thoroughly until it is of uniform consistency prior to application.
- For thinning, use Drinking Water only.

8 SAFETY

- Refer to SDS.